

Industrial Spark Plugs: Specifications

	7302	7303	7305	7306	7307	7308	7311	7313	7315	7321	7322	
10 Digit	0 242 356 501	0 242 356 502	0 242 356 503	0 242 356 504	0 242 356 507	0 242 356 508	0 242 255 512	0 242 236 580	0 242 255 519	0 242 255 511	0 242 255 518	0 241 256 524
Availability	Available	Available	Available	Available	Q2 2012	Available	Available	Available	As of Q3/2012	Available	As of Q3/2012	Available
Hex	7/8" (22.2 mm)	7/8" (22.2 mm)	7/8" (22.2 mm)	7/8" (22.2 mm)	13/16" (20.8 mm)	13/16" (20.8 mm)	13/16" (20.8 mm)	13/16" (20.8 mm)	13/16" (20.8 mm)	5/8" (16 mm)	5/8" (16 mm)	13/16" (20.8 mm)
Thread	18 mm	18 mm	18 mm	18 mm	18 mm	18 mm	14 mm	14 mm	14 mm	14 mm	14 mm	14 mm
Reach	13/16" (20.6 mm)	1/2" (12.7mm)	13/16" (20.6 mm)	13/16" (20.6 mm)	13/16" (20.6 mm)	13/16" (20.6 mm)	3/4" (19 mm)	3/4" (19 mm)	3/4" (19 mm)	3/4" (19 mm)	3/4" (19 mm)	3/4" (19 mm)
Heat Range	3	3	3	3	3	3	3	7	3	3	3	3
Center Electrode	0.8 mm Platinum/Iridium	0.8 mm Platinum/Iridium	2.4 mm Iridium	2.0 mm Platinum/Iridium	2.0 mm Iridium	2.4 mm Iridium	2.0 mm Platinum/Iridium	Copper with Yttrium	2.4 mm Iridium	1.25 mm Iridium	2.4 mm Iridium	0.8 mm Platinum
Ground Electrode	Platinum Inlay	Platinum Inlay	2.4 mm Iridium	Platinum Inlay	Platinum Inlay	2.4 mm Iridium	Platinum Inlay	Nickel	2.4 mm Iridium	Platinum Inlay	2.4 mm Iridium	Platinum
Gap	0.011" (0.3 mm)	0.011" (0.3 mm)	0.011" (0.3 mm)	0.011" (0.3 mm)	0.011" (0.3 mm)	0.011" (0.3 mm)	0.011" (0.3 mm)	0.020" (0.5 mm)	0.011" (0.3 mm)	0.011" (0.3 mm)	0.011" (0.3 mm)	0.011" (0.3 mm)
Resistance	3 kOhm	6 kOhm	6 kOhm	3 kOhm	3 kOhm	6 kOhm	6 kOhm	6 kOhm	6 kOhm	6 kOhm	6 kOhm	1 kOhm



Double Ir



Double Ir



Double Ir



Double Ir

